

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-91

SEED DIVIDER (BOERNER TYPE)

To reduce the size of a grain/seed sample into two equal halves, each exactly half of the original sample. The body and inner parts are made of copper and brass, so no chance of rust. The legs & supports are made of chrome plated steel.

Size : 86 cms height X 38 cms dia (approx)

No. of Pockets : 38

Supplied with two sample pans

The bottom section of the divider is removable for cleaning and pockets are visible from the top.



SAN-ST-91

SAN-ST-92

SEED BLOWER (DACOTA TYPE)

The air flow is very precisely controlled to obtain even the most difficult sensitive air separations. All the controls are mounted on the top panel including the timer for easy access. It has two sizes of columns for covering the entire range of seeds / grains. Balanced suitable blower fitted on the table, which is made of seasoned woods and fitted with caster wheels for portability.

Size : 48 X 56 X 86 cm (approx)

Operating Voltage : 220V, 50 Hz, AC

Small Tube Set : Recommended for brome, red top, blue grass, legumes, small cereal grains etc.

Size : 7.6 cm dia X 93 cm length and 4.5 cm dia X 93 cm length

Large tube set : Recommended for larger capacities and for grain, grass, legumes, corn, soyabean etc

Size : 10 cm dia X 93 cm height approx



SAN-ST-92

SAN-ST-93

PRECISION SEED DIVIDER (GAMET TYPE)

Divider is used for mixing & dividing grain samples. It performs accurately & similarly on all grains, seeds etc. Division and mixing are carried out by centrifugal action of motor driven revolving neoprene disc positioned under hopper. The sample falls from hopper on to the revolving disc and is evenly split into two similar samples.

Size : 38 X 31 X 51.5 ht cms (approx)

Hopper capacity : 2 Kg.

All wearing parts are made of brass and copper, body of high finish stainless steel, base of cast iron duly painted. Inside smooth finish eliminates sticking of samples to inner surfaces. Hopper and cylinder top lift off together providing easy access to interior parts. It is operated on 220V, 50 Hz., single phase electric motor of suitable capacity



SAN-ST-93



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-94

SEED DIVIDER RIFFLE TYPE (SOIL TYPE)

suitable for dividing or halving dry materials. Material poured into hopper is divided in two equal divisions and discharged alternatively in opposite directions into separate pans.

No. of chutes: 12, width of chutes: 1.2cm, Nos. of Pan: 2, hopper size: 28 X 21.5 cms It is supplied with steel pans, scoop and cleaning brush. Hopper and chutes made of stainless steel. Body, pans and scoop made of high quality steel duly painted to give best possible rust protection.



SAN-ST-94

SAN-ST-95

SEED SIEVE SHAKER (TABLE TOP)

Works on 220/230 volts AC, fitted with a FHP motor, it can accommodate 8 sieves of 8" dia. Speed is regulated through a continuously variable speed regulator fitted to the unit. One blank bottom pan with tie rod,

-----do----- same as above but dia. is 12"

OPTIONAL ACCESSORIES

Automatic 0-60 minute "German" Timer



SAN-ST-95

SAN-ST-96

SEED GRINDER

For grinding the seed in determination of moisture content. All contact parts should be made of stainless steel 304 grade. Constructed of non-absorbent material. Ground material is protected from ambient air during grinding, to the maximum extent possible. Grinder Size: 75x 25 mm, Motor: 0.5HP, Capacity: 5 gm-250 gms, Voltage: 220-240 AC, 50-60 Hz.

100x50 mm

0.50 H.P.

200x75 mm

1.00 H.P.



SAN-ST-96

SAN-ST-97

ILLUMINATED STAND MAGNIFIER

It is provided with versatile stand & illumination having large size (130 mm diameter).

SAN-ST-98

SEED TRIERS OF DIFFERENT SIZES (3 PER SET)

Made of mild steel, used for taking samples from bags of paddy, rice, wheat etc.

SAN-ST-99

SEED HERBARIUM CABINET

Made of CRC Sheet with 5 Nos. compartments in columns and 4 nos. in rows, with separate lock for each compartment.

Size of the Herbarium Cabinet is 18" x 30" x 72"

SAN-ST-100

GERMINATION TRAYS

Stainless Steel non corrosive of size: 45 x 45 x 10 cm, 25 x 25 x 6 cm



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-101

TESTING HUSKER

Used for easy husking of paddy, either in the laboratory or in the rice mill. Husked rice the husk and the immature paddy are automatically separated by an aspirator. Single phase built in motor. Cap.on paddy 50 Kg./hr. Size of rubber roller 35x100mm (width x area)



SAN-ST-101

SAN-ST-102

RICE TESTING MILL (RICE POLISHER)

In this machine 2-3 handfull grains can be tested and polished in a short time. It is provided with single phase motor with grinding wheels for polishing the grain and is provided with sieve for removal of bran. works on 220V, 50hz AC



SAN-ST-102

SAN-ST-117

RICE LAB MILL

Consist of husker, a wind turbine, a rice polisher, transmission and controlling components. Hard steel construction with open layout Easy maintenance Two steps process - first step is husking and second step is whitening. Suitable to measure: brown rice rate,

white rice rate and broken rice rate.

Maximum Paddy Sample Weight

Grinding Rice Sample Weight

Roller Diameter

Turning Speed of Fast Roller

Emery Roller Diameter

Turning Speed of Slow Roller

Turning Speed of Emery Roller

Turning Speed of Wind Turbine

Grinding Time

Turning Speed of Motor

Motor Power

Working Power Supply Along with 5 KVA automatic voltage stabilizer with input voltage range from 150 – 280 volts.



SAN-ST-117

MINI RICE MILL UNIT (WITH CLEANER, SHELLER AND POLISHER)

SAN-ST-117 (A)

RICE HUSKER / HULLER

Model : LM 24 2C

Made of steel sheet duly painted Motor operated with v belt pulley, Cyclone etc.,

Capacity :5 Qtl/ hr.



SAN-ST-117 (A)



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-117 (B)

RICE POLISHER

Model : TQN 118 RICE M

The machines have characteristics of stable operation and good appearance

Large yield the rice is white and bright

Less chaff low temperature of rice, low broken rate

Has better effect of par boiled rice and boiled rice.

Capacity (t / h) : 0.8 – 1.5 Power (kw) : 11 – 15

Speed of the main shaft (rpm) : 900

Amount of air sucking (m3/h) : 3720

Weight : 180 Kg

Shell size (mm) : 1060 x 470 x 1360



SAN-ST-117 (B)

SAN-ST-117 (C)

PADDY SEPERATOR / CLEANER

Model : MGCZ 100 x 6

Large yield Compact construction easy maintenance small required area Suitable for various kinds of rice and mixtures.

Capacity : 1.0 to 1.5 Ton

Power 1.1 K.W.



SAN-ST-117 (C)

SAN-ST-118

GRAIN GRADER / CLEANER

330-800 Kg/ hr with single phase with suitable motor

SAN-ST-115

PULLMAN TYPE THRESHER

Multi crop thresher 5 HP Motor -do- 5 HP Diesel Engine Operated

SAN-ST-116

LABORATORY INDENTED CYLINDER SEPERATOR

Quick change, variable speed cylinder drive vibrating conveyor for lifting discharge. Two collection trays, continuous cleaning cap. of 100-150kg./hr. on wheat feeding through electro magnetic vibratory feeder.



SAN-ST-116

SAN-ST-103

16 GRAIN - MOISTURE METER

Portable Rugged Construction, Microprocessor based, works on 12V Battery Direct Reading of Moisture percentage. Suitable for 16 grains i.e. Battery Canola corn flax, oats, Rice (2), Rye Rice, Wheat (4) Rye, Soyabean, Sunflowers (2), Sorghum, Automatic Compensation for variable due to temperature, with battery



SAN-ST-103

SAN-ST-103 (A)

39 GRAIN - MOISTURE METER

Portable but for 39 grains instead of 16 grains



An ISO 9001:2015 CERTIFIED CO.



SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-103 (B)

SEEDS MOISTURE METER

Based on resistance principal of measurement, Moisture meter working on a single chip computer (Micro controlled) concept. Grains includes wheatt rice, paddy, sorghum, beans, black gram, oil seeds, vegetable seeds and cereals, pulses, millets & more
Range : 3.5 to 40%, Consistency: $\pm 0.2\%$ Display : Digital, 3 digit LED, Automatic calibration. Low battery indication. Power AC mains/ 9V battery. Weight : aapprox 9.5 kg.



SAN-ST-103(B)

SAN-ST-103 (C)

SEEDS MOISTURE METER WITH DATALOGGING


---do--- same as above but with RS-232 indicator for Computer/ printer attachment & facility for record data in terms of moisture percentage, temp. commodity name along with date and time.

SAN-ST-104

SEED GARDER (LAB MODEL)

It is a very light and precise machine and is very useful for laboratory tests. When used as a grader the top screen is used for scalping and the bottom for grading. By changing the screen size the same machine can be used as Paddy Cleaner. Provided with 10 nos. screens and 2 nos. trays. Provided with $\frac{1}{2}$ H. P. single phase motor

Size : 80 x 54 x 75cm. (approx.)
Weight : 39 Kg.
Operating Voltage : 220V, 50 Hz., A. C.
Screen Area : 38 x 25.4cm. (approx.)



SAN-ST-104

SAN-ST-105

DIGITAL WOOD MOISTURE METER

Range : up to 30% Digital Display, with RS 232 Interface Battery operated

SAN-ST-106

SEED CABINET (FOR STORAGE OF SEED)

Made of Steel duly painted, Tray size : 12" x 12" x 4", Each tray has 3 compartment
CABINET SIZE : 10 tray, 20 tray, 30 tray

SAN-ST-107

SEED DRYER

Double Walled, Inner made of stainless steel, outer made of Mild Steel duly powder coated painted, Properly insulated, Provided with metallic insulated door with best quality hinges, handle suynthetic gasket, etc. Inner chamber is provided with perforated shelves, Chamber is provided with heating elements made of Kanthal wire with Temperature. Indicator Temperature from ambient to 60°C. Controlled by Digital Temperature indicator-cum-controller. Provided motorized air blower system. Mounted on wheels. **Size : 4'x3'x3'**



An ISO 9001:2015 CERTIFIED CO.



SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-107 (A)

SEED DRYER (DEHUMIDIFIER BASED)

Double walled, mounted on sturdy angle iron frame. Inner made of thick stainless Sheet duly painted with high temperature aluminum paint, outer made of heavy duty PCRC duly primer coated and enamel painted. Properly insulated. Temp. range is from ambient to 60°C with an accuracy of $\pm 2^\circ\text{C}$ and is controlled by digital temperature indicator cum controller with exhaust shaft on the top of the body. Dehumidification is done with non-cyclic, rotary type drier The Embry. desiccant honeycomb rotor media is adsorbent, non toxic, non flammable, water washable, having metal silicate desiccant synthesized in-site, on an in-organic fiber substrate, with net organics less than 2%. The desiccant rotor have a perimeter flange, and have .teeth.



SAN-ST-107

located around the perimeter, to ensure a positive and slip free rotation with a positive drive mechanism. The process and reactivation motors shall be of the TEFC to tally enclosed fan cooled) type. **TRAY CAP : 10 Trays, Size of Trays : 32 x 16 x 1.25"**

—do—Same as above but with Temperature maintained at 15°C - 30°C through refrigeration system

SAN-ST-108

SEED DISPLAY STAND

Made of Acrylic, Single Type
-do- Double grooved



SAN-ST-108

SAN-ST-109

SEED COUNTER (DIGITAL)

Total seeds to be counted : Max 99999

Maximum grains size to be counted

(Max Diameter is 1mm-15 mm)

Sensitivity adjustment 2 levels

Display : Alphanumeric LCD 2 line display Silent operation and small footprint

Counting speed : 35 to 300 grains/ Min Net weight : 8 Kgs

Power supply : 220 Volts, 50 Hz

Operating Mechanism : The Electromagnetic vibratory action to moves the seeds upward along the track. As a seed travels down the chute, it is detected by a electronic photo sensor.



SAN-ST-109



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-110

ILLUMINATED PURITY WORK BOARD

Made of wooden board with lacquer polish & provided with Milky sheet with magnifying glass & bulb etc. Light glows below the rectangular milky sheet. Cabinet is provided with drawer. Magnifying glass is adjustable and covers with the surface of milky sheet.

Size : 50 x 28 x 10 cms.(Ht.)



SAN-ST-110

SAN-ST-111

PORTABLE BAG CLOSER

Single Thread Chain Stitch, Versatile, fast, economical



SAN-ST-111

SAN-ST-112

MAIZE SHELLER

Manual & Hand operated, made from Cast Iron duly painted -do- with Mounted on wooden stand with Sieve System



SAN-ST-112

SAN-ST-113

MAIZE SHELLER (MOTOR OPERATED)

Made from cast iron, duly painted, provided with spring system to accommodate all sizes of cobs. operated through V belt, Pulley etc. With Electric Motor 1HP Crompton Make. The hole is mounted in powder coated cabinet with wheels, works on 220V Single Phase AC.



SAN-ST-113

SAN-ST-114

SINGLE PLANT THRESHER

For Single Plant, with 1/2 HP motor V-belt pulley, etc.

SAN-ST-119

SEED SIZE ANALYZING DIAL CALLIPER

Analog measuring device for measurement of length



SAN-ST-119

SOIL AUGER, DUTCH DESIGN ONE METER LONG WITH HANDLE

SAN-ST-121 (A) 5 cm dia

SOIL AUGER POST HOLE TYPE, ONE METER LONG WITH HANDLE

SAN-ST-121 (B) 5 cm dia, 10 cm dia, 15 cm dia
Extension Rod, 1 meter long with screw type fitting

SAN-ST-127

INFILTROMETER APPARATUS

Provided with one inner ring 30 cm dia, one outer ring 45 cm dia (height of rings 30cm), Driving plate with hammer weight and hammer guide rod, water level gauge



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEED & SOIL TESTING EQUIPMENTS

SAN-ST-120

TENSIOMETER

Specification: Standard model, fitted with suction meter 0-100 centibar vacuum, with screw able ceramic tip and translucent head assembly with insertion coring tool, tensiometer gauge recording charts and hand suction tensiometer priming syringe:

Tensiometer Size : 15cm, 30cm, 45cm, 75cm, 90cm

ACCESSORIES

Tensiometer insertion coring tool

Hand suction Tensiometer priming syringe

Tensiometer gauge recording chart (monthly) - pack of 12

SPARES

Standard Model Screwable ceramic tip

'O' Ring for Tensiometer Cup



SAN-ST-120

SAN-ST-122

SOIL CORE SAMPLER

For taking undisturbed soil samples in stainless steel soil sample rings (60mm dia, 100cc internal volume, complete with 10 stainless steel soil sampling rings with end caps, and one nylon headed shock absorbing hammer

ACCESSORIES

Stainless steel soil sample ring, 60mm dia, 100cc internal volume, with end caps

Nylon headed shock absorbing hammer

SAN-ST-123

SOIL MOISTURE SAMPLE BOX (ALUMINUM)

Size: 3" dia x 1" height (pack of 10 boxes)

Size: 4" dia x 1.25" height (pack of 10 boxes)

SAN-ST-124

SOIL MOISTURE METER

Digital Type, Instruments is calibrated in percentage saturation in soil and read from 0-100%, operated on 9 Volts cell digital display with an accuracy of $\pm 1\%$.



SAN-ST-124

SAN-ST-125

BRIX HYDROMETER WITH THERMOMETER

0 /10, 10/20, 20/30, 30/60, AT 20°C or 27.5°C

SAN-ST-126

SOIL THERMOMETER

Mercury in glass, in a rigid brass stem (hard chrome plated) with pointed end for smooth entry into soil. Range 0-50 deg. C minimum division 0.20176oC with fused bulb for quick response to temperature changes.

Stem Length 15 cm

Stem Length 20 cm



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

LEAF AREA METER (DIGITAL)

SAN - YMJ-C



The system of intelligent leaf area meter consists of a backlight apparatus and a tablet computer embedded application software (android). It is used for measuring leaf area and other values.
System: Android4.2.2 above
Size: 7inch full-color touch-screen
Rear camera: 800million
Resolution: 1920*1200

LEAF AREA METER (PORTABLE)

Measuring range : leaf area, average area, length of leaf, leaf width.
Measuring unit : Millimeter and Square centimeter
Length < 1000 mm
Width < 160 mm
Thickness < 8 mm
Storage : 200 groups with RS-232 Interface

SAN - YMJ-B



GRAIN MOISTURE METER

SAN - LDS-1H



Measuring error: d" 0.5% (main moisture range)
Measuring range: 3-35%
Sampling mode: basis weight 150g (except special samples)
Working compensation: automatic
Working environment: 0-40°C
Calibration: floating 3 points calibration, unlimited sample

GRAIN MOISTURE METER

Measuring object: non-metallic granulated materials such as cereal, wheat, rapeseed, soybean, vegetable seeds, corn, feed and so on
Measuring error: d" ± 0.5 % (main moisture range)
Measuring range: 3-35%
Temperature compensation: automatic
Attached function: volume-weight conversion display, sample weight display, temperature display, average moisture content calculation.
Calibration: 4 points calibration, unlimited sample (20 common varieties have been calibrated in advance, can be tested directly).
Working power: AC/DC, DC6V (4AA dry batteries)/special external power adapter

SAN - LDS-1G



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SANCO

SEED COUNTER

Microcomputer automatic control, press key are touches, complete automated operation. LED shows the hypothesis number and the actual number. Count speed can change, no noise, the precision is higher. Digital, complete automated operation, changeable counting speed, reset key, automatic stop button, speed regulation option, LED display, thumb wheel switches, digital counter speed regulator, detachable pan, high sensitive sensor.

TECHNICAL SPECIFICATION

Measuring range: 1-99999

Application scope:

Small sample: 0.7 - 4mm x 0.7-12mm

Big sample: 3 - 10mm x 3-12mm

Time for test: more than 1000/3minute

Precision: big sample: 2/1000

Small sample: 4/1000

Power: 220V 50HZ

SAN - SLY-C



SEED COUNTER HIGH ACCURACY

SAN - SLY-D



with 4G SD card, data can be stored without limits, be able to connect to PC, with the weighing function. Count number range: 1-99999 (LED display)

PLANT NUTRIENT ANALYZER

Index : Nitrogen, Chlorophyll and leaf temperature

Nitrogen scale : Full scale

Nitrogen Accuracy : +5%

Chlorophyll range : 0.0 to 99.9 SPAD

Chlorophyll accuracy : ± 2 SPAD

Leaf Temperature range : 0-90 OC

Leaf Temperature Accuracy : ± 0.5 OC

SAN - TYS-3N



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

VACUUM SEED COUNTING AND PLACING APP

Used for seed counting, suction and placing in the course of seed germination. Made up of main machine, suction tube and suction head with control button to control the suction power according to seed size. With 5 different seed suction heads, its size and specification match with Petri dish, meet needs of different seed germination.

Temperature: 40 °C

Power: 1200W 220V/50Hz

Voltage: 220V/50HZ

Machine size: 300*250*400 mm

Suction plate: 5pcs

Suction size: 13*19 (100 Holes, 50 holes/pc) 11.5*11.5 (100 holes, 2pcs), Ø8(100 holes/pc)

Vacuum planting plates

SAN - ZLC-2000



SEED BLOWER

SAN - CFY-II



Wind speed is adjustable according to granule size can achieve the best effect, and can be timed.

Max air volume: 3.8m³/min

Max wind pressure: 1300 pa

Noise: d"50db

Timing: 0-10min

Power: 180W, 220V 50HZ

LAB SIEVE SHAKER (WITH ONE SET OF SIEVE)

Max sieving quantity range: 500g

Sieving frame level: 3 layers

Sieving range: 100mm

Rotation speed: 115±5r/min

Sieve diameter: 220mm (grain sieve should buy separately)

Power: 60W AC220V 50Hz

Weight: 13kg

Package Size: 42*45*31CM

SAN - DSX



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

MULTI-RICE, WHEAT & CORN THRESHER

SAN - TLS-150A

It is a small electric threshing cleaning machines used in the laboratory for wheat, corn and so on grain threshing. The machine satisfies the threshing, cleaning, sorting and separation for grain



LAB WHIRLWIND MILL

SAN - FS-II



Suitable for making grinding samples, efficiently and rapidly grind wheat, corn, rice, mung bean, soybean and so on.

SOIL MOISTURE METER

SAN - TZS-1K

Hand-held meter Directly test and display soil moisture content.



SOIL HARDNESS METER

SAN - TYD-2



Maximum load: 100Kg (Kg and N can be switched automatically).

Resolution: 0.01Kg.

Accuracy: $\pm 0.5\%$.

Measuring depth: 0~450mm.

Power, charging power supply: 220V/AC,

Continuous operating time of battery, 6~8 hours

Stability, temperature drift: $0.2\mu V/^{\circ}C$ (0-60 $^{\circ}C$), Null drift, \

d" 0.1%/8 hours / FS Calibration range: full-scale calibration.

Ambient temperature: 0~ 60 $^{\circ}C$.

Ambient humidity: d" 80%.

Allowable overload: 150%.

Power supply mode: 5 nickel cyanogens battery /220V AC
charge 4~6hour



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SOIL WATER POTENTIAL METER

Max load: 100kpa
Resolution: 0.01kpa
Accuracy: ± 1
Soil Temperature testing range: $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Temperature accuracy: ± 0.5
Probe quantities: 3
Can test both soil water potential index and soil temperature index

SAN - TRS-II



PLANT CHLOROPHYLL METER

SAN - TYS-A



Quick & easy measurement of chlorophyll levels in plants leaves
Measuring area: 10mm
Measuring mode: 2-wavelength concentration difference of optical methods
Sensors: Silicon semiconductor photodiode
Display mode: measuring value: 3 digits liquid crystal display
Measuring times: 2 digits liquid crystal display
Min measuring interval : < 2s
Measuring Range: 9.9-199.9 SPAD
Accuracy: ± 1.0 SPAD
Repeat: ± 0.3 SPAD
Operating temperature: $0-50^{\circ}\text{C}$
Storage temperature: $-20-55^{\circ}\text{C}$

LEAF THICKNESS METER

Measure range: $0 \pm 6\text{mm}$;
Resolution: 0.01mm;
Accuracy: 0.015mm;
Contact area: $\phi 10\text{mm}$; Pointed type

SAN - YH-1



GERMINATION BOX

SAN - GB-101



Big
Small

13x19x12cm
12x12x6cm



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
Sec.-7, Rohini, Delhi-110085



Office : 8130700602
Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
sanco_lab@yahoo.com



www.sancolabs.com

SEMI-AUTOMATIC KJELDAHL NITROGEN ANALYZER (DISTILLATION PART)

Test varieties: grain, food, dairy products, drink, animal food, soil, medicine, settling, chemical and so on.
 Number of testing sample: solid <5 pieces , liquid <15ml
 Measurement Range: 0.1mgN-200mgN (0.02%-95%)
 Water Inlet Mode: running water and distilled water, wide use coverage
 Recycle Rate: $\geq 99\%$ (relative error, including digest process)
 Repeat Rate: relative standard error $< \pm 1\%$
 Distilled speed: 5-15min/sample (according to sample amount)
 Time for cooling water: 3L/Min



SAN - KDN

AUTOMATIC KJELDAHL NITROGEN ANALYZER (DISTILLATION PART)

SAN - ZDDN-II



Measure variety: foodstuff, feedstuff, foods, dairy products, drink, soil, water, medicine, precipitate and chemical.
 Storing data: 250 datum
 Measure range: 0.1mgN-200mgN (nitrogen content 0.02%-99%)
 Recovery rate: $100 \pm 1\%$ (relative error, include digestion process)
 Repetition rate: relative standard deviation $< \pm 1\%$
 Working hours: distillation time: 5-15 minutes
 Voltage: AC 220V, 50Hz, 1000W
 Cooling water consumption: distillation fraction 3L /min (water temperature is less than 20 degrees)
 Water temperature: $< 20^{\circ}\text{C}$

DIGESTION BLOCK

Adopts quartz infrared heating pipe, the radiation is primary and the conduction is auxiliary; short heating time, high efficiency
 Temperature controlling mode: digital
 Temperature control range: room temperature- 600°C
 Temperature control accuracy: $\pm 1^{\circ}\text{C}$
 Heating speed: $30^{\circ}\text{C}/\text{min}$
 Measurement range: 0.1mgN-200mgN (mg nitrogen)
 Measurement quantity: measure several varieties simultaneously at a time 20holes
 Digest time: 60-90 min/batch (according to sample quantity)
 Digestive pipe capacity: 300ml
 Temperature control accuracy: $\pm 1^{\circ}\text{C}$
 Power: 1000W/1500W/2500W

SAN -KDN-20C



An ISO 9001:2015 CERTIFIED CO.

SANDEEP INSTRUMENTS & CHEMICALS



68-69, Pocket C-7, 3rd Floor,
 Sec.-7, Rohini, Delhi-110085



Office : 8130700602
 Tele Fax : 91-11-27040602



sanco_lab@hotmail.com
 sanco_lab@yahoo.com



www.sancolabs.com